CHRISTIE INSPIRE SERIES

DWU760-iS / DWU860-iS / DWU960-iS / DWU960ST-iS

Boardrooms | Classrooms | Conference rooms | Museums

Performance-built, full-featured laser projectors

Our Christie® Inspire Series is a family of feature-rich laser projectors designed for classrooms, boardrooms and other small or mid-sized environments. With onboard Christie Twist™ warping and blending and optional Christie Mystique™ automated camera-based alignment software, it's fast and easy to set up, align, and recalibrate multi-projector arrays. Add the reliability, performance, and operational life of 1DLP® and laser illumination, and the Inspire Series offers amazing value without sacrificing advanced capabilities.

Unbeatable value

Featuring an advanced 1DLP laser illumination system, the Inspire Series provides up to 20,000 hours of reliable, virtually maintenance-free operation for a worry-free, low total cost of ownership.

Backed by an industry-leading five-year warranty* and with a price-point that won't break your budget, the Inspire Series is the easy choice for 7,000 to 9,600 lumen projectors.

Focused on features and quality

Proof that budget-friendly projectors don't need to sacrifice capabilities, the Inspire Series employs a robust platform that stands up to the demands of professional applications. Featuring flexible input/output options, two on-board 10W speakers, built-in warping and blending, and a lightweight and dust-resistant design with whisper-quiet operation, the Inspire Series delivers incredible value.



		DWU760A-iS (TAA)			
Technical specifi	cations	DWU760-iS	DWU860-iS	DWU960-iS	DWU960ST-iS
Image	brightness	• 6,000 ANSI lumens • 7,150 ISO lumens	• 7,200 ANSI lumens • 8,500 ISO lumens	• 8,100 ANSI lumens • 9,600 ISO lumens	• 8,100 ANSI lumens • 9,600 ISO lumens
	contrast ratio	• Full On/Off 1300:1 • 3,000,000:1 with Christie RealBlack™ technology enabled			
Display technology	type	• 1-chip 0.67" DMD \$600HB			
	native resolution	• WUXGA (1920 x 1200) 16:10 aspect ratio			
Illumination	type	• High-efficiency blue laser phosphor			
	performance	• 20,000 hrs to 50% brightness			
Inputs		• HDMI (1.4a) • HDMI 2.0 • HDBaseT • 3D Sync In (BNC) • VGA • Audio In (3.5mm phone jack) • USB-A • IR Reciever			
Outputs		• 3D Sync Out (BNC) • HDMI • Audio Out (3.5mm phone jack)			
Warping and blending	standard	• Embedded Christie Twist™ warping and blending			
	optional	• Christie Mystique™ automated camera-based alignment (download Mystique Lite Edition at no additional cost)			
TAA compliant		• Yes • No			
Speakers		• 2 x 10W			
Lens	type	• 1.25-2.0:1 (1.6x throw ratio) motorized lens - powered zoom, focus and offset • 0.65-0.75:1 (1.1x zoom) motorized lens - powered zoom, focus and offset coom, focus and offset			
	lens offset	• Vertical +/- 110% • Horizontal +/- 50% • Vertical +/- 100% • Horizontal +/- 30%			
Displayable scanning frequency	scan rates	• Horizontal: 15.375-91.146 KHz • Vertical: 24-85 Hz (120Hz for 3D feature)			
	max pixel clock rates	• 594 MHz (4096 x 2160); 162 MHz (1600 x 1200)			
Accessories	standard	Power cable • Lens cover (only for DWU960-iS); lens decoration ring (all other models) IR remote control (batteries included)			
	optional	• Christie Intelligent Camera (CIC) • Dust filter • WiFi dongle • 3.5mm cable for wired remote functionality			
Power requirements	operating voltage	• AC 100-240V, 50/60Hz			
	power consumption	• 500W	• 660W		
	operating current	• 5A	• 6.5A		
Audible noise		• 25dBA-30dBA depending on the mode used	• 27dBA-34dBA depending on the mode used	27dBA-36dBA dependin on the mode used	g
Physical	size	• (LxWxH): 18.9 x 16 x 5.7" (480 x 406 x 157mm)			
	shipping size	• 25.75 x 22.17 x 14.69" (654mm x 563mm x 373mm)			
	weight	• 29.8lbs (13.5kg)	• 30.2lbs (13.7kg)		
	shipping weight	• 36.8 lbs. (16.7kg)	• 37.9 lbs. (17.2kg)	• 37.4 lbs. (17 kg)	
Enviroment	temperature	• 0-40°C			
	humidity	• 10-85% RH			
	altitude	• 0-2,500ft at 0-40 C • 2,500-5,000ft at 0-35 C • 5,000-10,000ft at 0-30 C			
Regulatory		Contact Christie for the timing of certifications: UL/CSA/IEC 60950-1, FCC Class A, CE, FDA, CCC, KC, PSE, CU, SABS, BIS, VCCI, RCM, Ukr, SASO. This product conforms to all relevant European directives, standards, safety, health and environmental concerns RoHS, REACH, WEEE			
Warranty		Models with part numbers ending -02 and above: 5-years parts and labor on the projector Models with part numbers ending -01: 3-years parts and labor on the projector * three-years or 20,000 hours parts and labor on the illumination system Refer to the Christie ProAV standard limited warranty Or contact an authorized Christie representative for full details of our limited and extended warranties			

DWII760A-IS (TAA)

The performance you need

- 24/7 performance For continuous 'all day, every day' operation with industry-proven components that help ensure reliability
- > **IP5X dust-resistant** The airtight optical engine resists dust particles, ensures long-lasting reliability, and almost zeromaintenance performance
- Eco Mode Reduces brightness to 50%, significantly extends the lifetimes of your projector, and results in quieter operation (noise level)

For the most current specification information, please visit christie digital.com $\,$

Copyright 2024 Christie Digital Systems USA, Inc. All rights reserved. Our centers of excellence for manufacturing in Kitchener, Ontario, Canada and in Shenzhen, China are ISO 9001:2015 Quality Management System-certified. All brand names and product names are trademarks, registered trademarks or tradenames of their respective holders. "Christie" is a trademark of Christie Digital Systems USA, Inc., registered in the United States of America and certain other countries. DLP® and the DLP logo are registered trademarks of Texas Instruments. Performance specifications are typical. Due to constant research, specifications are subject to change without notice. CD4410-Inspire-Series-Datasheet-Mar-24-EN

- › Built-in warping, blending, & alignment Christie Twist™ and Mystique™ compatibility, for manual or automated camera-based warping, blending, and alignment
- Compatible with Christie Intelligent Camera (CIC) Triggers autofocus, automatically calibrates projector color, optimizes color uniformity, and more
- AMX and Crestron connectivity For enhanced collaboration and easy integration into virtually any existing boardroom





